

We claim:

Sub A

1. A display apparatus comprising:  
a primary display device for a computer; and  
at least one secondary display device for the computer, the at least one  
secondary display device operatively coupled to the computer and stored in a  
housing adjacent to the primary display device, such that the at least one secondary  
display device can be extended from the housing and used to display information for  
the computer.

Sub B

2. The display apparatus of claim 1, wherein the at least one secondary display  
device is operatively coupled to the primary display device

3. The display apparatus of claim 1, wherein the at least one secondary display  
device is held in an extended position with a spring loaded switch when the at least  
one secondary display device is extended from the housing.

4. The display apparatus of claim 3, wherein the spring loaded switch provides a  
conductive path for a transmission of a reconfiguration signal to the computer when  
the at least one secondary display device is extended from the housing.

5. The display apparatus of claim 4, wherein the computer reconfigures the  
primary display device and the at least one secondary display device to provide  
single session support upon receiving the reconfiguration signal, independent of a  
restart of the computer.

6. The display apparatus of claim 1, wherein the at least one secondary display  
device is extended from a side of the housing.

7. The display apparatus of claim 1, wherein the at least one secondary display device is operatively coupled to the computer through a flat printed cable (FPC).

8. The display apparatus of claim 1, wherein the at least one secondary display device and the primary display device are operatively coupled to the computer through a single inverter board.

9. The display apparatus of claim 1, wherein the primary display device and the at least one secondary display device are each operatively coupled to the computer through a single inverter board using a single FPC.

10. The display apparatus of claim 1, wherein the primary display device is operatively coupled to the computer through a single inverter board using a first FPC and wherein the at least one secondary display device is operatively coupled the computer through the single inverter board using a second FPC.

11. The display apparatus of claim 1, wherein the at least one secondary display device includes a first secondary display device extended from a side of the housing and a second secondary display device extended from a top of the housing.

12. The display apparatus of claim 1, further comprising at least one hinge coupling the at least one secondary display device to the housing.

13. A system comprising:  
a computer;  
a primary display device operatively coupled to the computer; and  
at least one secondary display device operatively coupled to the primary display device and stored in a housing behind the primary display device, such that the at least one secondary display device can be extended from the housing and used to display information for the computer.

Sw B 14. The system of claim 13, wherein the at least one secondary display device is held in an extended position with a spring loaded switch when the at least one secondary display device is extended from the housing.

5 15. The system of claim 14, wherein the spring loaded switch provides a conductive path for a transmission of a reconfiguration signal to the computer when the at least one secondary display device is extended from the housing.

10 16. The system of claim 13, wherein the at least one secondary display device is extended from a side of the housing.

17. The system of claim 13, wherein the at least one secondary display device is extended from a top of the housing.

15 18. The system of claim 13, wherein the at least one secondary display device is operatively coupled to the computer through a flat printed cable (FPC) cable.

20 19. The system of claim 13, wherein the primary display device and the at least one secondary display device is operatively coupled to the computer through a single inverter board using a single FPC.

25 20. The system of claim 13, wherein the primary display device is operatively coupled to the computer through a single inverter board using a first FPC and wherein the at least one secondary display device is operatively coupled the computer through the single inverter board using a second FPC.

30 21. The system of claim 13, wherein the at least one secondary display device includes a first secondary display device extended from a side of the housing and a secondary display device extended from a top of the housing.

22. A system comprising:  
a computer;  
a primary display device operatively coupled to the computer;  
at least one secondary display device operatively coupled to the primary  
display device and stored in a housing behind the primary display device, such that  
the at least one secondary display device can be extended from the housing and used  
to display information for the computer; and

a reconfiguration module located in the computer, comprising machine  
readable instruction for causing the computer to perform a method, wherein the  
reconfiguration module is initiated when the at least one secondary display device is  
extended from the housing, the method including:

displaying a reconfiguration screen on the primary display device, the  
reconfiguration screen including a number of reconfiguration options;

receiving one of the number of reconfiguration options based on a  
user input; and

reconfiguring the computer such that the computer displays  
information in the at least one secondary display device and the primary display  
device based on the one of the number of reconfiguration options.

23. A method for displaying, comprising:  
extending at least one secondary display device from a housing, wherein the  
housing is located behind a primary display device; and  
displaying information at the at least one secondary display device and the  
primary display device that is received from a computer that is operatively coupled to  
the at least one secondary display device and the primary display device.

24. The method of claim 23, further comprising storing the at least one secondary  
display device behind the housing for the primary device.

25. The method of claim 23, further comprising transmitting a reconfiguration signal to the computer when the at least one secondary display device is extended.

26. The method of claim 23, further comprising reconfiguring the computer to display to both the at least one secondary display device and the primary device.

27. The method of claim 23, wherein extending the at least one secondary display device from the housing includes extending the at least one secondary display device from a side of the housing.

28. The method of claim 23, wherein displaying information received from the computer that is operatively coupled to the at least one secondary display device and the primary display device includes transmitting the information through a single inverter board using a single FPC to the primary display device and the at least secondary display device.

29. The method of claim 23, wherein extending the at least one secondary display device from the housing includes extending a first secondary display device from a side of the housing and extending a second secondary display device from a top of the housing.

30. A method for displaying, comprising:  
detecting when at least one secondary display device is extended from a housing, wherein the housing is located behind a primary display device;  
transmitting a reconfiguration signal to a computer operatively coupled to the at least one secondary display device and the primary display device; and  
reconfiguring the computer such that the computer displays information in the at least one secondary display device and the primary display device.

31. The method of claim 30, further comprising displaying a reconfiguration screen on the primary display device and wherein reconfiguring the computer is based on a user input received from the reconfiguration screen.

5 32. A method for displaying, comprising:

storing at least one secondary display device in a housing located behind a primary display device;

extending the at least one secondary display device from the housing;

10 detecting when at least one secondary display device is extended from a housing;

transmitting a reconfiguration signal to a computer when the at least one secondary display device is extended, the computer operatively coupled to the at least one secondary display device and the primary display device; and

15 reconfiguring the computer such that the computer displays information in the at least one secondary display device and the primary device.

add a4  
ADD B2